STABILITY OF A PRISMATIC BAR UNDER THE INFLUENCE OF A COMPRESSIONAL STRAIN WAVE

by

WILLIAM H. HOPPMANN, 2nd

Navy Contract NONR-248(12)

Technical Report No. 7

Department of Mechanical Engineering
The Johns Hopkins University
Baltimore, Md.

June, 1952

STABILITY OF A PRISMATIC BAR UNDER THE

INFLUENCE OF A COMPRESSIONAL STRAIN WAVE

W. H. Hoppmann, 2nd

The Johns Hopkins University,

Baltimore, Md.

June, 1952

STABILITY OF A PRISMATIC BAR UNDER THE
INFLUENCE OF A COMPRESSIONAL STRAIN WAVE

In this paper a study is made of critical strain distributions introduced into a bar by dynamical loading in an axial direction. Transverse vibrations of the bar which may result from this type of loading are not investigated. It is considered that they are really involved in an extension of the problem.

The theory is developed in some detail for cases of bars of elastic material having Hookean or Non-Hookean stress-strain laws. Also, consideration is given to the case of the bar in the plastically deformed state.

One of the conclusions from the study is that the proposed method for determining critical states of strain suggests a means for experimentally investigating various plastic wave theories. Assuming tentatively a given theory of plastic strain propagation into the bar the critical strain distribution may be calculated. Indications of plastic buckling may then be investigated. The buckled shapes should also provide information on the theory of wave propagation.

INTRODUCTION

There is a growing interest in the problem of structures subjected to dynamic loads of the transient type. These loads are sometimes produced by collision or explosion. The column is an important structural element that may be subjected to this kind of force. The case of periodic axial loads of the steady-state vibration type has been considered by Stoker and Lubkin (1). The column compressed by the moving head of a testing machine has been treated by Hoff (2). In these cases the load is considered to vary with time but to be the same at all sections of the column at any one time. In other words, waves of compressional strain are not considered. In the present paper a study will be made of the compressional strain waves.

If the stress is not proportional to strain we may define the one-dimensional strain in the manner of von Kármán (3):

$$\frac{\partial \sigma}{\partial \epsilon} \cdot \frac{\partial^2 u}{\partial x^2} = \rho \frac{\partial^2 u}{\partial t^2} \qquad \dots\dots\dots\dots\dots [1]$$

If stress is proportional to strain the one-dimensional wave equation may be written in the usual manner:

$$E \cdot \frac{\partial^2 u}{\partial x^2} = \rho \frac{\partial^2 u}{\partial t^2} \qquad \dots\dots\dots\dots\dots [2]$$

With given initial and boundary conditions for a bar these equations may be solved. At any time t a determinable stress distribution σ_x exists in the bar.

As can easily be shown the differential equation for the transverse vibration of a longitudinally loaded bar of variable stiffness per unit length may be written:

$$\frac{\partial^2}{\partial x^2}\left(EI \frac{\partial^2 w}{\partial x^2}\right) + \frac{\partial}{\partial x}\left(P \frac{\partial w}{\partial x}\right) + \rho A \frac{\partial^2 w}{\partial t^2} = 0$$

$$\dots\dots [3]$$

If we consider $[1]$ or $[2]$ and $[3]$ simultaneously we define possible transverse displacements induced by the compressional strain wave. In order to obtain a first criterion of instability it is proposed to neglect the acceleration term in $[3]$ and determine P which is a function of x and of t from $[1]$ or $[2]$. The merit of these assumptions will be investigated in a series of experiments at a later date.

The D'Alembert principle can be used and the $\rho \frac{\partial^2 u}{\partial t^2}$ considered as reversed effective forces putting the bar in statical equilibrium along its length. This

principle provides a means of determining the load distribution along the bar or column at any time. We may then consider a force at the wave front, a force at the externally loaded end, and a distribution of forces between these two points. The force corresponding to each differential length is $\rho A\, dx\, \dfrac{\partial^2 u}{\partial t^2}$. This theory will be illustrated by three cases.

CASE I

ELASTIC CONDITION, HOOKEAN STRESS-STRAIN LAW

Assume a straight bar initially unstressed and with certain given boundary conditions. The material of the bar is elastic with a linear stress-strain law. A compressive load as a known function of time is suddenly applied at one end. If numerical methods of solution are to be avoided, and they would be quite clumsy in a problem of this type, analytical solutions must be obtained. Many of these can be found in the literature. The simplest will now be considered (4).

In Fig. 1 a simply supported bar of length 1 is shown with a force P applied at one end and the front of the strain wave progressed to a distance x_o from that end. Assume that the force P is caused by a large mass M moving with constant velocity v_o. Then the strain $\in_x$ will be constant and of magnitude given by

$$\in_x = \in_o = \frac{v_o}{c}$$

where c is the constant velocity with which the strain moves into the bar (5).

The principle of D'Alembert will now enable us to translate this problem into an equivalent static one for any given time t. The corresponding loading for this case is then shown in Fig. 2.

Fig. 1. Simple strain wave in bar

Fig. 2. Equivalent loading

In region ① there is no strain since the strain wave has not progressed into that portion of the bar as yet. In Region ②, there is constant strain of magnitude $\frac{U_o}{c}$ at each point and loads of magnitude $AE\frac{U_o}{c}$ at each of its extremities.

The two differential equations for bending of the bar are:

$$EI \frac{\partial^4 w}{\partial x^4} = 0 \qquad\qquad \text{Region ①} \ldots \ldots [4]$$

$$EI \frac{\partial^4 w}{\partial x^4} + P \frac{\partial^2 w}{\partial x^2} = 0 \qquad\qquad \text{Region ②} \ldots \ldots [5]$$

Solution of $[4]$ is:

$$W_1 = A_1 x^3 + B_1 x^2 + C_1 x + D$$

and solution of $[5]$ is

$$W_2 = A_2 + B_2 x + C_2 \sin \lambda x + D_2 \cos \lambda x$$

The Boundary and continuity conditions are:

$$W = 0, \qquad \frac{\partial^2 w}{\partial x^2} = 0 \qquad \text{for } x_1 = 0 \qquad \text{---- } [6]$$
$$W = 0, \qquad \frac{\partial^2 w}{\partial x^2} = 0 \qquad \text{for } x_2 = 0$$

$$\left. \begin{array}{l} W_1 = W_2 \\[6pt] \dfrac{\partial W_1}{\partial x} = - \dfrac{\partial W_2}{\partial x} \\[6pt] \dfrac{\partial^2 W_1}{\partial x^2} = \dfrac{\partial^2 W_2}{\partial x^2} \\[6pt] \dfrac{\partial^3 W_1}{\partial x^3} = - \dfrac{\partial^3 W_2}{\partial x^3} \end{array} \right\} \quad \begin{array}{l} \text{for } x_1 = \ell_1 \\ \quad\ x_2 = \ell_2 \end{array} \text{---- } [7]$$

The vanishing of the determinant of the system of the 8 linear equations in the 8 constants A_1, B_1, C_1, D_1, A_2, B_2, C_2, D_2 gives the instability equation:

$$\ell_1 \lambda \cos \lambda \ell_2 + \sin \lambda \ell_2 = 0 \qquad \dots\dots\dots\dots [8]$$

For convenience we may put

$$\ell_1 + \ell_2 = \ell, \quad \ell_2 = f\ell, \quad \text{and} \quad \lambda \ell = \beta$$

then equation [8] becomes:

$$(1-f)\,\beta \cos \beta f + \sin \beta f = 0 \qquad \dots\dots\dots\dots [9]$$

By means of equation [9] the following table of critical loads is determined.

TABLE I.

f	β	$\beta^2 = \dfrac{P_{cr}\,\ell^2}{EI}$
0.	∞	∞
.1	16.35	268.3
.2	8.55	73.0
.3	6.01	36.1
.4	4.76	22.7
.5	4.06	16.4
.6	3.62	13.1
.7	3.36	11.2
.8	3.21	10.3
.9	3.15	9.9
1.0	3.14	9.9

$$P_{cr} = \beta^2 \frac{EI}{\ell^2} \qquad \dots\dots\dots\dots [10]$$

It is readily seen that a relationship has been established between the fractional length factor f and the critical load P_{cr} given by [10]. If reflections of the strain wave occur before the critical stress is attained, the process must be repeated with appropriate strain distributions and another table of f values.

CASE II

ELASTIC CONDITION, NON-HOOKEAN STRESS-STRAIN LAW

In thecase of bars made of non-Hookean materials the stress-strain law is non-

Fig. 3.   Stress-strain law as two straight line segments

Fig. 4.   Strain distribution in bar

linear, but the materials may still be elastic. A simple example of such a stress-
strain relation is shown in Fig. 3.

As an example of this case suppose a force is applied at one end of a straight
bar so that the load is constant in time and produces a stress, at the end of the
bar, which lies between σ_1' and σ_2' in Fig. 3. In this case a wave of stress
of magnitude σ_1' propagates at a known speed into the bar. This wave is followed
by a slower one of magnitude σ_2' as shown in Fig. 4. In Fig. 5 the equivalent
static loading at some time t is shown.

In region ① the load is a force (P_1+P_2) in region ② the load is P_1 and
in region ③ there is no load as the wave front has not penetrated this region as
yet. This strain propagation satisfies the differential equation [1] . The dif-
ferential equations of lateral bending are:

$$
\begin{aligned}
E I \frac{\partial^4 w}{\partial x^4} + (P_1 + P_2) \frac{\partial^2 w}{\partial x^2} &= 0 \qquad \text{Region ①} \\
\\
E I \frac{\partial^4 w}{\partial x^4} + P_1 \frac{\partial^2 w}{\partial x^2} &= 0 \qquad \text{Region ②} \\
\\
E I \frac{\partial^4 w}{\partial x^4} \qquad\qquad &= 0 \qquad \text{Region ③}
\end{aligned} \right\} \cdots [8]
$$

The solutions are:

$$W_1 = A_1 + B_1 x + C_1 \sin \lambda_1 x + D_1 \cos \lambda_1 x$$

$$W_2 = A_2 + B_2 x + C_2 \sin \lambda_2 x + D_2 \cos \lambda_2 x \qquad \Bigg\} \quad \cdots \cdots [9]$$

$$W_3 = A_3 x^3 + B_3 x^2 + C_3 x + D$$

The boundary and continuity conditions are:

$$W = 0, \qquad \frac{\partial^2 W}{\partial x^2} = 0 \qquad \text{for } x_1 = 0 \qquad \Bigg\} \quad \cdots [10]$$

$$W = 0, \qquad \frac{\partial^2 W}{\partial x^2} = 0 \qquad \text{for } x_3 = 0$$

and

$$W_1 \big|_{x=\ell_1} = W_2 \big|_{x=\ell_2}$$

$$\frac{\partial W_1}{\partial x} \bigg|_{x=\ell_1} = -\frac{\partial W_2}{\partial x} \bigg|_{x=\ell_2}$$

$$E_2 \frac{\partial^2 W_1}{\partial x^2} \bigg|_{x=\ell_1} = E_1 \frac{\partial^2 W_2}{\partial x^2} \bigg|_{x=\ell_2}$$

$$E_2 \frac{\partial^3 W_1}{\partial x^3} \bigg|_{x=\ell_1} = -E_1 \frac{\partial^3 W_2}{\partial x^3} \bigg|_{x=\ell_2} \qquad \Bigg\} \quad \cdots \cdots [11]$$

$$W_3 \big|_{x_3=\ell_3} = W_2 \big|_{x_2=0}$$

$$\frac{\partial W_3}{\partial x} \bigg|_{x_3=\ell_3} = \frac{\partial W_2}{\partial x^2} \bigg|_{x_2=0}$$

$$\frac{\partial^2 W_3}{\partial x^2} \bigg|_{x_3=\ell_3} = \frac{\partial^2 W_2}{\partial x^2} \bigg|_{x_2=0}$$

$$\frac{\partial^3 W_3}{\partial x^3} \bigg|_{x_3=\ell_3} = \frac{\partial^3 W_2}{\partial x^3} \bigg|_{x_2=0}$$

The venishing of the determinant of the system of 12 linear homogeneous equations in the 12 constants gives the instability equation:

$$\lambda_2^2 \left(\lambda_1^2 \lambda_2^3 \sin \lambda_1 \ell_1 \cos \lambda_2 \ell_2 + \lambda_1^3 \lambda_2^2 \sin \lambda_2 \ell_2 \cos \lambda_1 \ell_1 \right)$$
$$+ \ell_3 \lambda_2^3 \left(- \lambda_1^2 \lambda_2^3 \sin \lambda_1 \ell_1 \sin \lambda_2 \ell_2 + \lambda_1^3 \lambda_2^2 \cos \lambda_1 \ell_1 \cos \lambda_2 \ell_2 \right)$$
$$= 0 \quad \cdot \cdot \cdot \cdot \cdot \cdot \cdot \cdot \cdot \cdot [12]$$

We may divide equation $[12]$ by $\lambda_1^2 \lambda_2^2$ and determine the roots for various ratios σ_2 / σ_1 and E_2 / E_1. As an example suppose:

$$\sigma_2 / \sigma_1 = 2 \quad \text{and} \quad E_2 / E_1 = 1/2$$

Then we may write as follows:

$$c_1 t = \ell_1 + \ell_2 \quad , \quad c_2 t = \ell_1$$

$$c_2 = \sqrt{\frac{E_2}{\rho}} \quad , \quad c_1 = \sqrt{\frac{E_1}{\rho}}$$

$$c_1 / c_2 = \frac{\ell_1 + \ell_2}{\ell_1} = \sqrt{\frac{E_1}{E_2}} = 1 + \frac{\ell_2}{\ell_1}$$

so $\quad \dfrac{\ell_2}{\ell_1} = \sqrt{\dfrac{E_1}{E_2}} \; -1$

$$\ell_1 + \ell_2 + \ell_3 = \ell \quad \text{and so} \quad \ell_3 = \ell - \ell_1 - \ell_2$$

Then

$$\ell_2 = \left[\sqrt{\dfrac{E_1}{E_2}} - 1\right]\ell_1$$

$$\ell_3 = \ell - \ell_1 - \left[\sqrt{\dfrac{E_1}{E_2}} - 1\right]\ell_1$$

Then let $1_1 = f\ell$ where f is a fractional parameter.

so $\quad \ell_2 = \left[\sqrt{\dfrac{E_1}{E_2}} - 1\right]f\ell$

$$\ell_3 = \left\{1 - f - \left(\sqrt{\dfrac{E_1}{E_2}} - 1\right)f\right\}\ell$$

For the assumed ratios E_1/E_2 and σ_1/σ_2 we have

$$P_1 + P_2 = 2P_1$$

$$\lambda_1^{\,2} = 4\dfrac{P_1}{E_1}$$

$$\lambda_2^{\,2} = \dfrac{P_1}{E_1}$$

so

$$\lambda_1 = 2\lambda_2$$

and

$$\ell_1 = f\ell, \quad \ell_2 = \left[\sqrt{2} - 1\right]f\ell,$$

$$\ell_3 = \left\{1 - \sqrt{2}\,f\right\}\ell$$

Fig. 5. Equivalent static loading

Fig. 6. Non-linear stress-strain curve of strain
hardenable material

Obviously the maximum allowable f in this formulation is given by

$$1 - \sqrt{2}\, f = 0$$

Then we may construct a table of values relating critical loads to lengths.

TABLE II

f	$\lambda_2 \ell$	$(\lambda_2 \ell)^2 = \dfrac{P_1 \ell^2}{E_1 I}$	$\lambda_1 \ell = 2 \lambda_2 \ell$	$(\lambda_1 \ell)^2 = \dfrac{(P_1 + P_2)\ell^2}{E_2 I}$
.1	7.48	55.90	14.96	223.6
.2	3.94	15.40	7.88	61.6
.3	2.78	7.70	5.56	30.8
.4	2.24	5.00	4.48	20.0
.5	1.94	3.75	3.88	15.0
.6	1.76	3.09	3.52	12.4
.7	1.65	2.71	3.30	10.8
.7071	1.64	2.68	3.28	10.7

Obviously for any given force P, the critical fractional length f is determined. The shape of the bent bar is given by equations $[9]$. Again in this case if reflections of the strain wave occur before the critical stress is attained the process must be repeated with appropriate strain distributions and another table of f values.

CASE III

PLASTIC CONDITION

The differential equation of the strain in bar in the plastic region exhibiting unloading phenomenon may be written as noted by T. von Kármán

$$\frac{\partial \sigma}{\partial \epsilon} \cdot \frac{\partial^2 u}{\partial x^2} = \rho \frac{\partial^2 u}{\partial t^2}$$

where $\dfrac{\partial \sigma}{\partial \epsilon}$ is the slope of the stress strain curve and ρ is the density. It is claimed that the velocity of such a plastic wave is

$$C = \sqrt{\frac{1}{\rho} \frac{\partial \sigma}{\partial \epsilon}}$$

and the static engineering stress-strain curve for the material may be used to determine $\dfrac{\partial \sigma}{\partial \epsilon}$ for any given ϵ .

As an example suppose that a bar shown in Fig. 1 is subjected to a constant stress σ_o at one end. Then it is asserted that a plastic wave of intensity σ_o progresses into the bar at velocity

$$c = \sqrt{\frac{1}{\rho} \frac{\partial \sigma}{\partial \epsilon}}$$

In order to determine instability in this case for a material exhibiting strain-hardening, we may use the method of Engesser (6) to take account of unloading.

Recalling the method of Engesser an effective modulus is determined for the bar section as in Fig. 7.

$$\frac{E_2 h_2}{\rho^*} \cdot \frac{h_2}{2} = \frac{E_1 h_1}{\rho^*} \cdot \frac{h_1}{2}$$

so $\qquad E_2 h_2^2 = E_1 h_1^2 \qquad$ which is the force equation

- 11 -

Fig. 7.   Distribution of stress in cross-section of bar

$$h_1 + h_2 = h$$

$$\tfrac{1}{2} h_1 \cdot \frac{E_1 h_1}{\rho^*} \cdot \frac{2h_1}{3} + \tfrac{1}{2} h_2 \cdot \frac{E_2 h_2}{\rho^*} \cdot \frac{2h_2}{3} = M$$

M is the moment at section.

If b is the width of the section

$$M = \frac{b h^3}{12 \rho} \cdot \frac{4 E_1 \cdot E_2}{\left[\sqrt{E_1} + \sqrt{E_2}\right]^2}$$

putting

$$E_r = \frac{4 E_1 \cdot E_2}{\left[\sqrt{E_1} + \sqrt{E_2}\right]^2}$$

and $M = \dfrac{E_r \cdot I}{\rho^*}$

If we now replace E by E_r we may revert to Case I for determining the length of loading section for any given applied end stress σ_o' which is critical.

DISCUSSION

The theory presented herein is proposed as a first criterion of instability of a prismatic bar with a transient force applied at its end. Although a complete and accurate equation describing strain wave propagation in a bar must include lateral contraction as well as other effects in the bar it is considered that the simplest one-dimensional wave theory serves the purpose of the present exposition. For a similar reason, the transverse inertia forces related to bending are neglected in order to get an approximate criterion of instability. It is considered that

The merit of these assumptions should be experimentally investigated, because very few data on the compression impact loading of bars occur in the literature. Some experiments by D. S. Clark (7) are quite suggestive of what may be expected in the way of sidewise plastic deformation of relatively long bars of lead subjected to dynamic loads on one end. A series of experiments will be conducted now by the author with the specific purpose of investigating sidewise deformation of bars subjected to impact loading on one end.

ACKNOWLEDGMENT

BIBLIOGRAPHY

1. "Stability of Columns and Strings under Periodically Varying Forces" by S. Lubkin and J. J. Stoker. Quarterly of Applied Mathematics, vol. I, October, 1943, No. 3, P. 215.

2. "The Dynamics of the Buckling of Elastic Columns" by N. J. Hoff, Journal of Applied Mechanics, vol. 18, No. 1, March 1951, P. 68.

3. "Plastic-wave Propagation Effects in High-speed Testing" by E. H. Lee and H. Wolf, Journal of Applied Mechanics, vol. 18, No. 4, December 1951, P. 385.

4. "Theory of Elastic Stability" by S. Timoshenko, McGraw-Hill Book Co., Inc., 1936, P. 112.

5. "Theory of Elasticity" by S. Timoshenko, McGraw-Hill Book Co. Inc., 1934, P. 384.

6. "Widerstandsmomente und Kernfiguren bei beliebigem Formänderungsgesetz (Spannungsgesetz)", by Fr. Engesser, Zeitschrift des Vereines Deutscher Ingenieure, 1898, Part 2, vol. 42, P. 927.

7. "The Propagation of Plasticity in Uniaxial Compression" by M. P. White and Le Van Griffis, Discussion by D. S. Clark, The Journal of Applied Mechanics, vol. 16, No. 2, June 1949, P. 219.

Chief of Bureau of Aeronautics
Navy Department
Washington 25, D. C.
Attn: TD-41, Technical Library (1)
: DE-22, C. W. Hurley (1)
: DE-23, E. M. Ryan (1)

Chief of Bureau of Ordnance
Navy Department
Washington 25, D. C.
Attn: Ad-3, Technical Library (1)

Chief of Bureau of Ships
Navy Department
Washington 25, D. C.
Attn: Director of Research (3)
Code 372 (1)
Code 442 (1)
Code 423 (1)

Chief of Bureau of Yards and Docks
Navy Department,
Washington 25, D. C.
Attn: Research Division (2)
Code C-313 (1)

Superintendent
Post Graduate School
U. S. Naval Academy
Annapolis, Maryland (1)

Director
Naval Research Laboratory
Washington 20. D. C.
Attn: Code 186, Technical Library (1)
Code 500, Mechanics Div. (2)

Naval Air Experimental Station
Naval Air Material Center
Naval Base
Philadelphia 12, Pa.
Attn: Head, Aeronautical Materials
Laboratory (1)

Superintendent,
Naval Gun Factory
Washington 25, D. C. (1)

Naval Ordnance Laboratory
White Oak, Maryland
RFD 1, Silver Spring, Md.
Attn: Dr. C. A. Truesdell (1)
Dr. D. E. Marlowe (1)

Naval Ordnance Test Station
Inyokern, California
Attn: Scientific Officer (1)
Structures Br. (Pasadena) (1)

Director,
David Taylor Model Basin
Washington 7, D. C.
Att: Structural Mech. Division (2)

Director
Naval Engineering Experiment Station
Annapolis, Maryland
Attn: (1)

Director,
Materials Laboratory
New York Naval Shipyard
Brooklyn 1, New York (1)

ARMY

Chief of Staff
Department of the Army
The Pentagon
Washington 25, D. C
Attn: Director of Research and
Development (1)

Office of Chief of Ordnance
Research and Development Service
Department of the Army
The Pentagon
Washington 25, D. C. (2)

Commanding Officer
Watertown Arsenal
Watertown, Massachusetts
Attn: Laboratory Division (1)

Commanding Officer
Frankford Arsenal
Philadelphia, Pa
Attn: Laboratory Division (1)

Contract
N6 ONR-243

Project
NR 035-215

Chief of Naval Research
Navy Department
Washington 25, D. C.
Attn. Code N 482   (11)

Commanding Officer
Boston Branch Office
Office of Naval Research
495 Summer St.,
Boston 10. Mass.   (1)

Commanding Officer
New York Branch Office
Office of Naval Research
50 Church St.,
New York 7, N. Y.   (1)

Commanding Officer
Chicago Branch Of.
Office of Naval Research
844 N. Rush St.,
Chicago 11, Ill.   (1)

Commanding Officer
San Francisco Branch Of.
Office of Naval Research
801 Donahue St.,
San Francisco, Cal.   (1)

Commanding Officer
Los Angeles Branch Of
Office of Naval Research
1030 E. Green St.,
Pasadena, Cal.   (1)

Asst. Naval Attache for Research
Naval Attache
American Embassy, Navy #100
c/o Fleet Post Office
New York, N. Y.   (5)

Contract Administrator
Southeastern Area
c/o Office of Naval Research
Washington 25, D. C.   (2)

Commanding Officer
Squier Signal Laboratory
Fort Monmouth, New Jersey
Attn: Components and Materials
            Branch   (1)

AIR FORCES

Commanding General
U. S. Air Forces
The Pentagon
Washington 25, D. C.
Attn: Research and Development
         Division   (1)

Commanding General
Air Materiel Command
Wright-Patterson Air Force Base
Dayton, Ohio
Attn: J. B. Johnson, Chief
     Materials Laboratory   (1)
     E. H. Schwartz (MCREXA-8) (2)

OTHER GOVERNMENT AGENCIES

U. S. Atomic Energy Commission
Division of Research
Washington, D. C.   (1)

Director,
National Bureau of Standards
Washington, D. C.
Attn: Dr. W. H. Ramberg   (2)

U. S. Coast Guard
1300 E. Street, NW
Washington, D. C.
Attn: Chief, Testing and Devel-
        opment Division   (1)

Forest Products Laboratory
Madison, Wisconsin
Attn: L. J. Markwardt   (1)

National Advisory Committee
     for Aeronautics
1724 F Street, N W
Washington, D. C.
Attn: Materials Research
    Coordination Group   (2)

National Advisory Committee
     for Aeronautics
Langley Field, Virginia   (1)
Attn: Mr. E. Lundquist
      Dr. S. B. Batdorf   (1)

National Advisory Committee for
     Aeronautics
Cleveland Municipal Airport
Cleveland, Ohio
Attn: J. H. Collins, Jr   (1)

U. S. Maritime Commission
Technical Bureau
Washington, D. C.
Attn: Mr. Wanless   (1)

Research and Development Board
       Library
Room 3 D 641
Pentagon Building
Washington, D. C   (2)

NAVY CONTRACTORS AND OTHER INVESTIGATORS ACTIVELY ENGAGED IN MECHANICS RESEARCH

Dr. S. P. Timoshenko
School of Engineering
Stanford University
Stanford University, California (1)

Dr. N. J. Hoff
Department of Aeronautical Engineering
     and Applied Mechanics
Polytechnic Institute of Brooklyn
99 Livingston Street
Brooklyn, New York   (1)

Dr. N. M. Newmark
Department of Civil Engineering
University of Illinois
Urbana, Illinois   (1)

Dr. J N. Goodier
School of Engineering
Stanford University
Stanford University, California (1)

Professor F. K. Teichmann
Department of Aeronautical
      Engineering
New York University
University Heights Bronx
New York City, New York   (1)

Professor L. S. Jacobsen
Stanford University
Stanford University California   (1)

Professor Jesse Ormendroyd
University of Michigan
Ann Arbor, Michigan   (1)

Dr. W. H. Hoppmann
Johns Hopkins University
Baltimore, Maryland   (10)

Professor B. J. Lazan
Syracuse University
Syracuse, New York   (1)

Professor E. Sternberg
Illinois-Institute of Technology
Technology Center
Chicago 16, Illinois   (1)

Dr. C. B. Smith
College of Arts and Sciences
Department of Mechanics
Walker Hall
University of Florida
Gainesville, Florida   (1)

UNCLASSIFIED